

TOWNSHIP OF FLORENCE

APPLICATION FOR STREET OPENINGS/CURB CUTS

DATE: _____

NAME OF PROPERTY OWNER: _____

ADDRESS OF PROPERTY OWNER: _____

LOCATION OF WORK PROJECT: _____

PURPOSE OF OPENING: _____

NAME OF CONTRACTOR OR PERSON PERFORMING THE WORK: _____

ADDRESS

PHONE NUMBER

APPLICATION FEE FOR STREET OPENING or CURB CUT = \$50.00

REQUIRED BOND FOR STREET OPENING or CURB CUT = \$600.00

TYPE OF ROAD, STREET, CURB, ETC. TO BE EXCAVATED/OPENED

_____ **BITUMINOUS CONCRETE**

_____ **BITUMINOUS MACADAM**

_____ **SHEET ASPHALT**

_____ **BRICK**

_____ **CONCRETE**

_____ **BITUMINOUS DRESSING**

_____ **EARTH SHOULDER**

_____ **UNIMPROVED**

DIMENSIONS OF AREA TO BE EXCAVATED:


WIDTH _____ **LENGTH** _____ **DEPTH** _____

SIGNATURE OF APPLICANT: _____

HOMEOWNER

CONTRACTOR

NOTE: A COPY OF THIS APPLICATION IS TO BE ATTACHED TO THE ISSUED PERMIT.



DETAIL PLAN
OF
STANDARD DRIVEWAY
FLORENCE TOWNSHIP N.J.

Chapter 126.

Article I. Excavations

§ 126-1. Permit required; fee.

[Amended 12-1-1993 by Ord. No. 1993-32]

It shall be unlawful for any person, company, firm or corporation to tear up, dig into, break up, displace or excavate any of the streets, sidewalks, curbs or gutters of the Township of Florence without first obtaining a permit therefor from the Township Clerk or her designee, who shall charge a fee of \$50 for each permit issued. A separate permit will be required for each opening made. Any such permit shall state the location and approximate size of the opening to be made. No permit shall be deemed to authorize anything not stated in the permit, and the person to whom it is issued shall confine his work within such limits so that the work of repaving shall be as small as possible.

§ 126-2. Commencement of work; extensions.

The work on any opening to be made under any such permit shall be commenced within 10 days from the date of such permit and the work prosecuted with due diligence to its completion. If, for any reason, work is not commenced within said period of 10 days, the permit shall be void, unless, within such period of 10 days, the applicant shall present the permit to the Township Clerk, who shall thereupon either return the deposit or extend the time for the beginning of said work for another period of 10 days by endorsement on the permit, and no permit so extended shall be valid unless the work thereunder is commenced within 10 days from the date of such endorsement.

§ 126-3. Surface restoration; backfilling.

Whenever any street, sidewalk, curb or gutter is broken up or excavated, it shall be restored at the expense of the person or persons making the opening, to the satisfaction of the Township Engineer or other duly authorized designee, in compliance with the following requirements:

A.

The excavation shall interfere as little as possible with travel along said street or road, and no greater part of any street or road shall be opened at any one time than the Township Engineer or other duly authorized designee shall allow in order to prevent such interference with travel.

B.

The backfilling of trenches shall be performed by the applicant under the supervision and direction of the Township Engineer or other duly authorized designee. Inspection for each street opening application shall be done in accordance with the directions of the Division of Engineering. The applicant shall notify the officer instructed to perform the inspection 24 hours before a street opening is ready for backfill, and the inspector shall have the right to, and it shall be his duty to, inspect said street opening and be present to continuously inspect the backfill and street surface restoration procedure. No backfill material, base material or surface material shall be placed in the opening until 24 hours after the aforesaid notice has been given. Less than 24 hours may be given in case of emergency openings.

C.

When the Township Engineer or other duly authorized designee is instructed to perform the inspection, the applicant shall pay to the township such reasonable fee as may be charged by the Engineer or other duly authorized designee for time actually spent in making such inspection.

D.

Neither such inspection nor anything else contained in this Article shall relieve the applicant from the duty to remedy any defect in such restoration of the opening as may then or thereafter appear or from any other liability for such defects.

E.

All fill material shall be deposited in layers not exceeding six inches, and each layer shall be rammed with approved pneumatic or power-driven mechanical tampers. Flat-faced mechanical tampers may be substituted for vibratory soil compactors where the shoring and bracing of trenches make the use of vibratory compactors impracticable. Shoring, bracing and sheathing shall be withdrawn as the filling proceeds. Fill material used in the first two feet of cover shall be made with earth, which shall be free from stones or rock fragments of a size larger than two inches. Broken stone to be used in replacing the stone base shall be cast in separate piles and kept clean and separated from other excavation material. The broken stone shall be carefully replaced to a minimum thickness of eight inches. If there is a deficiency in such thickness, it shall be made up by adding clean stone not less than two inches in diameter. The stone base shall be tamped and keyed with mineral filler. In openings where the existing base consists of gravel or native soil, a minimum of eight inches of pneumatically compacted Type 5 Grade A soil aggregate, as specified in the 1961 New Jersey State Highway Department Standard Specifications for Road and Bridge Construction, shall be placed on top of the backfill. In openings where the existing base consists of Belgian block, paving brick or concrete, the soil aggregate method for restoring the base shall be used.

F.

A temporary patch shall be constructed by the applicant consisting of a sand and asphalt patch mixture two inches thick and thoroughly tamped and rolled. The temporary patch shall be constructed within 24 hours after tamping of the backfill. When filled, the opening shall be flush with the existing contour of the road. Within a period of not less than four months nor more than six months, the applicant shall replace the temporary patch with permanent pavement.

G.

The temporary pavement shall be removed and additional soil aggregate placed to bring the excavation to grade where settlement has taken place. The openings shall be properly cleaned out and painted with asphaltic oil or tar, then filled with a hot-mixed, hot-laid bituminous concrete pavement, conforming to the FABC pavement specifications of the State Highway Department Specifications referenced in Subsection E hereof, thoroughly tamping and rolling the material to obtain a dense, smooth surface, flush with the existing road surface. The bituminous concrete surface, when compacted, shall have a minimum thickness of two inches. The surface of the permanent patch shall receive a wearing surface conforming to the existing road surface, unless directed otherwise by the Township Engineer or other duly authorized designee.

§ 126-4. Fees.

A.

No permit shall be granted by the Township Clerk until the applicant has paid to him the sum of \$50 in cash or certified check, drawn to the order of the Treasurer of the Township of Florence, if the opening is to be made in the bituminous concrete, bituminous macadam, sheet asphalt, brick or concrete surfaces and not wider than three feet in width. For excavation and street openings in excess of 20 square yards, the applicant shall pay to the Township Clerk the sum of \$2 per square yard for each additional square yard of excavation in excess of 20 square yards for improved streets and \$1.25 per square yard for each additional square yard of excavation in excess of 20 square yards. These sums shall be in addition to the above-mentioned amounts.

B.

The security required shall not be less than \$600 for each opening. Deposits shall be retained for six months, except for driveway openings, which may be released after 30 days following satisfactory inspection. Bond/deposit for street or curb opening: Bond will be required in a minimum amount of \$600, with a maximum amount of \$2,500, depending on the scope of the project and as recommended by the Township Engineer or his designee.

C.

This amount deposited under paragraph A shall be retained by the township for a period of six months from the date of the permit or from the date on which it is extended to guarantee the proper performance of the work done by the applicant and the maintenance thereof in good condition by the applicant. If the applicant shall fail to restore the street, sidewalk, curb or gutter involved to its proper condition as soon as practicable and within three days after the service or mailing of a notice from the Township Clerk so to do, then the Township Engineer or other duly authorized designee may cause such restoration to be made and pay the cost thereof from said deposit, or in case a bond has been filed in lieu of a cash deposit, the township shall collect the cost of such restoration from the applicant or bonding company. If, during such period of six months, the filling of the opening shall settle or any street surface over such opening shall require repairing and the applicant shall fail to make such repairs as are required within three days after the service or mailing of a notice from the Township Clerk so to do, then the Township Engineer or other duly authorized designee may cause such repairs to be made and pay the cost thereof from said deposit, or in case a bond has been deposited in lieu of a cash deposit, the township shall collect the cost of such repairs from the applicant or bonding company.