

**BUILDING DEPARTMENT
CITY OF DAVISON**

200 E. FLINT ST. SUITE 2

DAVISON, MI. 48423

Phone 810-653-2191/Fax 810-653-9621

www.cityofdavison.org

**APPLICATION FOR PLAN EXAMINATION
BUILDING/ZONING COMPLIANCE PERMIT**

INSTRUCTIONS: Applicants must complete all sections, including the Site Plan.

Application Date	Permit Type: (Check one) SEWER WATER ROW DRIVEWAY	Is Owner Applicant Yes No
------------------	---	-----------------------------------

\$1,500 SURETY BOND REQUIRED TO WORK IN THE RIGHT OF WAY

Note: Permits for Electrical, Mechanical, and Plumbing must be obtained thru the State of Michigan.

1. PROPERTY INFORMATION (Location where permit is being issued)

Street Address	Zoning	Parcel Type (Check one) Residential Industrial Commercial Other
Legal Description	Parcel No. 52-	

2. OWNER(S) INFORMATION

Owner(s) Name	Business Name	Phone
Email Address		
Street Address	City	State Zip Code

3. CONTRACTORS INFORMATION

Business Name	Contractor's License No.	Phone
Owner(s) Name	Federal Employer ID No.	
Address	City	State Zip Code
Email Address		
Workers Comp Insurance Carrier	MESC Employer Number (Or Reason for Exemption)	

4. CERTIFICATION

I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his or her authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued, I certify that the Code Official or the Code Official's authorized representative shall have the authority to enter the area covered by such permit at any reasonable hour to enforce the provision(s) of the Code(s) applicable to such permit.

Signature of Applicant	Email Address (if different from above)	
Responsible Person in Charge of Work	Title	Phone

DEPARTMENT USE ONLY

Prepared By: _____ Date: _____


Approved By: _____ Title: _____

Inspections Required: _____

5. SITE OR PLOT PLAN - For Applicant Use

(Show all lot lines, any easements and building layout and dimensions)

A large grid of graph paper, consisting of 30 columns and 40 rows of small squares, intended for drawing a site or plot plan. The grid is empty and occupies the majority of the page below the instructions.



City of Davison

200 E. FLINT STREET, SUITE 2
DAVISON, MICHIGAN 48423-1246

TELEPHONE (810) 653-2191
FAX (810) 653-9621

GUIDELINES FOR SEWER REPAIRS, REPLACEMENT OR INSTALL

CALL MISS DIG BEFORE DIGGING 811

- 1) A permit is required from city hall before the job can be stated.
- 2) A \$1,500.00 surety bond is required by contractor for any work done in the right-of-way and must be presented when obtaining permit. Bond will be held for one (1) year.
- 3) The DPW must do an inspection of all work performed **BEFORE ANY BACKFILLING**.
- 4) Inspections are done between the hours of 7:30 am and 2:30 pm, any inspections done outside these hours must be arranged with the DPW Director and will be billed for 2 ½ hours worked to do inspection for contractor.
- 5) There must be a bed of sand or pee-gravel under and up the spring line of any pipe put into the ground. Any excavation done under road-way, curbs, sidewalks, and driveways will be backfilled with sand compacted in one (1) foot intervals to obtain 95% compaction.
- 6) All work will be open trench excavation (no boring or tunneling) exceptions to this may be approved by the DPW Director.
- 7) Any needed cement/asphalt replacement due to excavation within the right-of-way will be done by the contractor. All work will be done per the specs set by the city.
- 8) Any portion not replaced must be videotaped (viewed by DPW) to verify it will not be an issue after repair is made.
- 9) All pipe installed will be of PVC schedule 40, SDR 26 or greater with all bell-ends laid up hill toward flow. All rubber couplings installed will be of Fernco reinforced type connection. Connections made at the main will be with Fenco Quickseal or double stainless steel strap tapping saddle. There shall be no bend greater than 45 degrees installed on the connection. There must be a least one (1) foot separation between two 45 degree bends. There shall not be any tee's installed. Clean out's shall be within 3 feet of structure and every 100 feet.
- 10) All job sites shall have barricading in place, in order to keep the excavation area and pedestrian and vehicle traffic safe. All barricading in the road way must be done to M-Dot traffic standards.
- 11) Whenever possible, the building sewer shall be brought to the buildings at an elevation below the basement floor. No building sewer shall be laid parallel to, or within three (3) feet of, any bearing wall that might thereby be weakened. The depth shall be sufficient to afford protection from frost. All excavations required for the installation of a building sewer shall be open trench work unless otherwise approved by the Inspector. 1044.024 BUILDING SEWER LOCATION

Any Questions contact DPW Director at (810)653-2191 or (810)577-3558