

DEPARTMENT OF PUBLIC WORKS
VILLAGE OF KENSINGTON
GREAT NECK, NEW YORK

PERMIT APPLICATION
(For Road Openings and Curb Cuts)

NO. _____

NAME OF APPLICANT _____

ADDRESS _____ TEL. NO. _____

NAME OF ROAD _____

TYPE OF PAVEMENT _____ WIDTH _____ FT. SHOULDERS _____

TYPE OF SIDEWALK _____ WIDTH _____ FT.

NO. OF OPENINGS _____ SIZE _____

OPENING ON SIDE OF ROAD (N. - S. - E. - W.) _____

SHOW LOCATION OF LINE BEING TAPPED SAME SIDE YES _____ NO _____

SHOW DISTANCE TO NEAREST CROSS ROAD AND NAME OF ROAD

WILL DRIVE PIPE UNDER PAVEMENT YES _____ NO _____

PURPOSE OF APPLICATION _____

SIGNATURE _____ TITLE _____

24 HOURS NOTICE MUST BE GIVEN PERMIT SECTION BEFORE STARTING WORK

NO TUNNELLING ALLOWED

SKETCH OF LOCATION

DRAW IN NORTH ARROW

P.L.

CURB

FEE \$ _____
DEPOSIT \$ _____
TOTAL \$ _____

PERMIT APPROVED _____ DATE _____

WORK APPROVED _____ DATE _____

(OVER)

VILLAGE OF KENSINGTON
SPECIFICATIONS FOR ROAD OPENING REPAIRS

All street excavations shall be backfilled with clean fill free of organic matter, well tamped, and shall be acceptable to the Building Insp.; and shall be covered with temporary asphalt pavement for a period not to exceed six months.

All street openings and curb and sidewalk alterations shall be protected with lights and barricades and shall not interrupt or endanger travel over Village streets.

No permanent pavement shall be replaced before two months have elapsed after backfilling the excavation.

The permanent pavement of asphalt roads shall consist of a 6-inch reinforced concrete slab surfaced with 2 inches of compacted plant mixed asphalt.

The concrete shall consist of portland cement, sharp, clean sand, and 3/4 inch broken stone or gravel mixed in 1-2-4 proportions.

The reinforcing shall be 6-inch by 6-inch new 6 welded wire road mesh.

The 2-inch asphalt surface shall be compacted with a power roller weighing not less than 5 tons.

The finished asphalt surface shall conform to the contours of the road and shall be sealed with liquid asphalt around the perimeter.

No permanent pavement shall be replaced in freezing weather.

All permanent pavement shall extend 12 inches beyond the original excavation where such excavation does not exceed 4 feet in depth, and shall extend at least 24 inches where the excavation exceeds 4 feet in depth. The edges of existing pavement when cut back must be straight and square.

The permanent pavement of concrete roads shall consist of an 8-inch reinforced concrete slab, with the concrete proportions and reinforcing as described above.

NOTICE

If the work under this permit has not started within 90 days from the issuance date, the permit shall be void.

To avoid serious damage to vital underground utility lines, please call 661-6000 before starting work and report all excavations.

Attention is called to Penal Law, Section 1918, requiring all persons excavating in existing streets to give 72 hours' notice to the Gas Distributing Utility or Agency.

Signature of Applicant