

Prescriptive Residential Alterations That Do Not Require HERS Field VerificationCEC-CF1R-ALT-05-E (Revised 01/19)
COMMISSION

CALIFORNIA ENERGY



CERTIFICATE OF COMPLIANCE	CF1R-ALT-05-E
Prescriptive Residential Alterations That Do Not Require HERS Field Verification	
Project Name:	(Page 1 of 8)
Page 1 of 8	Date Prepared:

This compliance document is only applicable to simple alterations that do not require HERS verification for compliance. When HERS verification is required, a CF1R-ALT-01 shall first be registered with a HERS Provider Data Registry.

Alterations to Space Conditioning Systems that are exempt from HERS verification requirements may use the CF1R-ALT-05 and CF2R-ALT-05 Compliance Documents. Possible exemptions from duct leakage testing include: less than 40 ft of ducts were added or replaced; or the existing duct system was insulated with asbestos; or the existing duct system was previously tested and passed by a HERS Rater. If space conditioning systems are altered and are not exempt from HERS verification, then a CF1R-ALT-02 must be completed and registered with a HERS Provider Data Registry.

Alterations that utilize close Cell Spray Polyurethane Foam (ccSPF) with a density of 1.5 to less than 2.5 pounds per cubic foot having an R-value greater than 5.8 per inch, or Open Cell Spray Polyurethane Foam (ocSPF) with a density of 0.4 to less than 1.5 pounds per cubic foot having an R-value of 3.6 per inch, shall complete and register a CF1R-ALT-01 with a HERS Provider Data Registry.

If more than one person has responsibility for installation of the items on this certificate, each person shall prepare and sign a certificate applicable to the portion of construction for which they are responsible. Alternatively, the person with chief responsibility for construction shall prepare and sign this certificate for the entire construction. All applicable Mandatory Measures shall be met. Temporary labels shall not be removed before verification by the building inspector.

A. General Information				
01	Project Name:		02	Date Prepared:
03	Project Location:		04	Building Front Orientation (deg or cardinal):
05	CA City:	WASCO	06	Number of Altered Dwelling Units:
07	Zip Code:	93280	08	Fuel Type:
09	Climate Zone:	13	10	Total Conditioned Floor Area (ft ²):
11	Building Type:	NA	12	Slab Area (ft ²):
13	Project Scope:	NA		

Project Name:	Page 2 of 8	Date Prepared:
---------------	-------------	----------------

B. Building Insulation Details (Section 150.2(b)1)

[illegible]

Prescriptive Residential Alterations That Do Not Require HERS Field Verification

CEC-CF1R-ALT-05-E (Revised 01/19)

COMMISSION

**CERTIFICATE OF COMPLIANCE**

CF1R-ALT-05-E

Prescriptive Residential Alterations That Do Not Require HERS Field Verification

(Page 3 of 8)

Project Name:

Page 3 of 8

Date Prepared:

C. Roof Replacement (Prescriptive Alteration, Section 150.2(b)1H)

01	02	03	04	05	06	07	08	09	10	11	12	13
Method of Compliance	Roof Pitch	Exception	CRRC Product ID Number	Product Type	R-value Deck Insulation	Proposed				Minimum Required		
						Initial Solar Reflectance	Aged Solar Reflectance	Thermal Emittance	SRI (Optional)	Aged Solar Reflectance	Thermal Emittance	SRI (Optional)

NOTES:

- Roof area covered by building integrated photovoltaic panels and solar thermal panels are exempt from the above Cool Roof requirements.
- Liquid field applied coatings must comply with installation criteria from Section 110.8(i)4.

D. Fenestration/Glazing Allowed Areas and Efficiencies (Section 150.2(b)1)

01	02	03	04		05		06		07
Alteration Type	Maximum Allowed Fenestration Area For All Orientations (ft ²)	Maximum Allowed West-Facing Fenestration Area Only (ft ²)	Existing Fenestration Area for All Orientations (ft ²)	Existing West-Facing Fenestration Area (ft ²)	Maximum Allowed U-factor (Windows)	Maximum Allowed U-factor (Skylights)	Maximum Allowed SHGC (Windows)	Maximum Allowed SHGC (Skylights)	Comments

Prescriptive Residential Alterations That Do Not Require HERS Field VerificationCEC-CF1R-ALT-05-E (Revised 01/19)
COMMISSION

CALIFORNIA ENERGY



CERTIFICATE OF COMPLIANCE		CF1R-ALT-05-E
Prescriptive Residential Alterations That Do Not Require HERS Field Verification		(Page 8 of 8)
Project Name:	Page 8 of 8	Date Prepared:
DOCUMENTATION AUTHOR'S DECLARATION STATEMENT		
1. I certify that this Certificate of Compliance documentation is accurate and complete.		
Documentation Author Name:	Documentation Author Signature:	
Company:	Signature Date:	
Address:	CEA/ HERS Certification Identification (if applicable):	
City/State/Zip:	Phone:	
RESPONSIBLE PERSON'S DECLARATION STATEMENT		
I certify the following under penalty of perjury, under the laws of the State of California:		
1. The information provided on this Certificate of Compliance is true and correct.		
2. I am eligible under Division 3 of the Business and Professions Code to accept responsibility for the building design or system design identified on this Certificate of Compliance (responsible designer).		
3. That the energy features and performance specifications, materials, components, and manufactured devices for the building design or system design identified on this Certificate of Compliance conform to the requirements of Title 24, Part 1 and Part 6 of the California Code of Regulations.		
4. The building design features or system design features identified on this Certificate of Compliance are consistent with the information provided on other applicable compliance documents, worksheets, calculations, plans and specifications submitted to the enforcement agency for approval with this building permit application.		
5. I will ensure that a registered copy of this Certificate of Compliance shall be made available with the building permit(s) issued for the building, and made available to the enforcement agency for all applicable inspections. I understand that a registered copy of this Certificate of Compliance is required to be included with the documentation the builder provides to the building owner at occupancy.		
Responsible Designer Name:	Responsible Designer Signature:	
Company :	Date Signed:	
Address:	License:	
City/State/Zip:	Phone:	

For assistance or questions regarding the Energy Standards, contact the Energy Hotline at: 1-800-772-3300.

CF1R-ALT-05-E User Instructions

NOTE: If more space is needed, print a duplicate page and fill in.

Minimum requirements for prescriptive alteration compliance can be found in Building Energy Efficiency Standards Section 150.2(b)1.

Completing these forms will require that you have the Reference Appendices for the 2019 Building Energy Efficiency Standards (P400-2018-020). This document contains the Joint Appendices which are used to determine climate zone and to complete the section for opaque surfaces. When the term CF1R is used it means the CF1R-ALT-05. Worksheets are identified by their entire name and subsequently by only the worksheet number, such as ENV-02.

Instructions for sections with column numbers and row letters are given separately.

If any part of the alteration does not comply, prescriptive compliance fails, in which case the performance compliance approach must be used in an attempt to achieve compliance.

A. General Information

1. Project Name: Identifying information, such as owner's name.
2. Date Prepared: Date of document preparation.
3. Project Location: Legal street address of property or other applicable identifying information.
4. Building Front Orientation: Building front orientation expressed in degrees, where North = 0, East = 90, South = 180, and West = 270. Indicate cardinal if it is a subdivision or multi-family project built in multiple orientations. The standards (section 100.1) include the following additional details for determining orientation:
 - Cardinal covers all orientations (for buildings that will be built in multiple orientations);
 - North is oriented to within 45 degrees of true north, including 45 degrees east of north;
 - East is oriented to within 45 degrees of true east, including 45 degrees south of east;
 - South is oriented to within 45 degrees of true south, including 45 degrees west of south;
 - West is oriented to within 45 degrees of true west, including 45 degrees north of west.
5. CA City: Legal city/town of property.
6. Number of Altered Dwelling Units: 1 for single-family, 1 or more for multifamily.
7. Zip Code: 5-digit zip code for the project location (used to determine climate zone).
8. Fuel Type: Natural Gas, Liquefied Propane Gas, or Electricity.

NOTE: Prescriptive compliance only allows electricity if natural gas is not connected to the building, or if the conditions of Section 150.2(b)1Hiii are met. See instruction at section H for more information.

9. Climate Zone: From Joint Appendix JA2.1.1.
10. Total Conditioned Floor Area: Enter the new conditioned floor area in ft², as measured from the outside of exterior walls of the dwelling unit or building being altered.
11. Building Type: Single Family (includes duplex), or Multi-Family (a building that shares common walls and common floors or ceilings).
12. Slab Area: Area of the first floor slab (if any) in ft².
13. Project Scope: Insulation, Roof Replacement, Fenestration/Glazing, Heating System, Cooling System, Duct System, and/or Water Heating System alteration.

B. Building Insulation Details (Section 150.2(b)1)

1. Tag/ID: A label (if any) from the plans, such as A1.4 or wall.
2. Assembly Type: Roof, Ceiling, Wall, or Floor.
3. Frame Type: Wood or Metal.
4. Frame Depth: Nominal dimensions of framing material in inches such as 2x4, 2x6, 2x8, 2x10.
5. Frame Spacing: 16, 24, or 48 inches on center.

6. Proposed Cavity R-value: Insulation installed between framing.

Proposed Continuous Insulation R-value: R-value of rigid or continuous insulation (not interrupted by framing). See Table 4.3.4. of Reference Appendices for metal frame construction.

NOTE: Section 110.8(d) specifies that if adding insulation to an existing attic, the resulting attic insulation must total R-22. However, the amount of insulation required is limited to the amount of room available for insulation without conflicting with Building Code Section 1203.2.

7. Proposed U-factor: The U-factor for the entire assembly.
8. Appendix JA4 Reference Table: Table number used to determine the R-value or U-factor (e.g., an attic assembly is 4.2.1).
9. Appendix JA4 Reference Cell: Cell number used to determine the R-value or U-factor (e.g., an R-38ceiling with 24-inch on center framing is A21).
10. Required U-factor: From the requirements in Sections 110.8 and 150.0.
11. Comments: Any notes regarding location, unique conditions, or attachments.

C. Roof Replacement (Prescriptive Alteration, Section 150.2(b)1H)

When 50% or more of the roof is being replaced the roofing requirements are triggered. Any areas of roof covered by building integrated photovoltaic panels and solar thermal panels are exempt, but the area of roof not covered by photovoltaic panels would still need to meet any applicable cool roof requirements. Additionally, there are many alternatives/exceptions to when a cool roof is required.

When the roof is steep slope (pitch greater than or equal to 2:12) the roof requirements include a cool roof in climate zones 10-15. The minimum requirement is 0.20 Aged Solar Reflectance, 0.75 Thermal Emittance, or a minimum SRI of 16.

1. Method of Compliance: Indicate if the method of compliance is going to be based on Aged Solar Reflectance and Thermal Emittance, the Solar Reflectance Index (SRI), or an Exception.
2. Roof Pitch: Expressed as 4:12, for example, which means the roof rises 4 foot within a span of 12 feet. When roofs have multiple pitches the requirements are based on the pitch of 50% or more of the roof.
3. Exception: If meeting one of the exceptions. Indicate which exception is, or will be, met.

EXCEPTIONS AND ALTERNATIVES FOR STEEP SLOPE ROOFS:

- (a) Mass roof 25 lbs/ft² or greater (uncommon situation such as sod roof);
- (b) Air space 1" from top of roof deck to bottom of roofing;
- (c) Roofing product has a profile ratio of rise to width of 1 to 5 for 50 percent or greater of the width of the roofing product;
- (d) Ducts already meet Section 150.1(c) insulation and duct leakage requirements;
- (e) Roof has R-38 insulation;
- (f) Roof has a radiant barrier;
- (g) No ducts are installed in the attic; or
- (h) R-2 insulation above the roof deck.

In climate zones 13 & 15, when there is a low slope roof (pitch less than 2:12) the cool roof requirements are for a minimum Aged Solar Reflectance of 0.63, a minimum 0.75 Thermal Emittance, or a minimum SRI of 75.

EXCEPTIONS AND ALTERNATIVES FOR LOW SLOPE ROOFS:

- (a) Mass roof 25 lbs/ft² or greater (uncommon situation such as sod roof);
- (b) No ducts are installed in the attic; or
- (c) Roof deck insulation—by installing roof deck insulation, a lower aged solar reflectance is required: R-2 (0.62-0.60), R-4 (0.59-0.55), R-6 (0.54-0.50), R-8 (0.49-0.45), R-12 (0.44-0.40), R-16 (0.39-0.35), R-20 (0.34-0.30), R-24 (0.29-0.25).

NOTE: If one of the exceptions above has been selected then the rest of Section C. is Not Required.

4. CRRC Product ID Number: The CRRC Product ID Number is obtained from the Cool Roof Rating Council's Rated Product Directory at www.coolroofs.org/products/results. Products are listed by manufacturer, brand, type of installation, roofing material, and color, as well as product performance.
5. Product type: See Cool Roof Rating Council's directory. Generally product types include single-ply roof, wood shingles, asphalt roof, metal roof, tile roof.
6. R-value Deck Insulation: If one of the exceptions selected includes adding roof deck insulation, indicate the R-value of the insulation.
7. Proposed Initial Solar Reflectance: Based on the product chosen from the Cool Roof Rating Council's Rated Product Directory. If using default assumption indicate N/A since the Aged Solar Reflectance is available.
8. Proposed Aged Solar Reflectance: Value is from the Cool Roof Rating Council's Rated Product Directory. If the aged value is not available, calculate the Aged Solar Reflectance using the Solar Reflectance Index (SRI) Calculator located on the California Energy Commission website or the aging equation $\rho_{aged} = [0.2 + \beta(\rho_{initial} - 0.2)]$, where $\rho_{initial}$ = the initial solar reflectance and soiling resistance β is listed by product type below.

VALUES OF SOILING RESISTANCE β BY PRODUCT TYPE